

SAFETY DATA SHEET POLYESTER GROUT (BASE COMPONENT)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name POLYESTER GROUT (BASE COMPONENT)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polyester resin-based mortar - resin component

1.3. Details of the supplier of the safety data sheet

Supplier PAREX Ltd
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2QZ
Tel: +44 (0)1827 711755
(Mon-Fri 08:30-16:30)
Fax: +44 (0)1827 711330
sds@parex.co.uk

1.4. Emergency telephone number

Emergency telephone + 44 (0)1827 711755 (Mon-Fri 08:30 - 16:30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 1 - H372

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs (Ears) through prolonged or repeated exposure.

POLYESTER GROUT (BASE COMPONENT)

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/ container in accordance with national regulations. P241 Use explosion-proof electrical/ ventilating /lighting/.../ equipment. P260 Do not breathe vapours.
---------------------------------	---

Contains UNSATURATED POLYESTER RESIN IN STYRENE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

UNSATURATED POLYESTER RESIN IN STYRENE	60-100%
CAS number: 100-42-5	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 1 - H372	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Harmful if inhaled. Irritating to respiratory system.
Skin contact	The product is strongly irritating to eyes and skin.
Eye contact	The product is strongly irritating to eyes and skin.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

POLYESTER GROUT (BASE COMPONENT)

Specific hazards	The product is flammable.
Hazardous combustion products	When heated, toxic and corrosive vapours/gases may be formed.
5.3. Advice for firefighters	
Protective actions during firefighting	Fight fire with normal precautions from a reasonable distance.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	No action shall be taken without appropriate training or involving any personal risk. Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains, water courses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	No smoking, sparks, flames or other sources of ignition near spillage. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
Advice on general occupational hygiene	Wash at the end of each work shift and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry and cool place.
Storage class	Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

UNSATURATED POLYESTER RESIN IN STYRENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm
 Short-term exposure limit (15-minute): WEL 250 ppm
 Long-term exposure limit (8-hour TWA): WEL 20ppm (Ireland)
 Short-term exposure limit (15-minute): WEL 40ppm (Ireland)
 WEL = Workplace Exposure Limit

UNSATURATED POLYESTER RESIN IN STYRENE (CAS: 100-42-5)

POLYESTER GROUT (BASE COMPONENT)

Ingredient comments Provide good ventilation and local exhaust in working area Due to the hazardous nature of ingredients, exposure should be minimal.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Wear eye protection.

Hand protection

Wear protective gloves.

Other skin and body protection

Avoid contact with skin.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Odour	Aromatic.
Initial boiling point and range	>145 C at 760mm Hg
Flash point	31C
Upper/lower flammability or explosive limits	1.1% to 6.1%
Auto-ignition temperature	490C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react strongly with the product: Peroxides.

10.4. Conditions to avoid

Conditions to avoid Keep away from heat, sparks and open flame.

10.5. Incompatible materials

10.6. Hazardous decomposition products

POLYESTER GROUT (BASE COMPONENT)

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (gases ppm) 4,500.0

ATE inhalation (vapours mg/l) 11.0

ATE inhalation (dusts/mists mg/l) 1.5

General information Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.

Inhalation The liquid may be irritating to eyes, respiratory system and skin. May cause nausea, headache, dizziness and intoxication.

Skin contact The product is strongly irritating to eyes and skin.

Eye contact The product is strongly irritating to eyes and skin.

Target organs Ears

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product is not identified as a PBT/vPvB substance

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information This material and its container must be disposed of as hazardous waste.

Disposal methods Dispose of contents/container in accordance with national regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1866

UN No. (IMDG) 1866

UN No. (ICAO) 1866

UN No. (ADN) 1866

14.2. UN proper shipping name

POLYESTER GROUT (BASE COMPONENT)

Proper shipping name (ADR/RID) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

Proper shipping name (IMDG) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

Proper shipping name (ICAO) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

Proper shipping name (ADN) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ADN packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

POLYESTER GROUT (BASE COMPONENT)

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by	QSHE Manager
Revision date	30/08/2018
Supersedes date	22/02/2018
SDS number	21053
Hazard statements in full	H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361d Suspected of damaging the unborn child. H372 Causes damage to organs (Ears) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.