

## SAFETY DATA SHEET

### Thinners 1031 Clear

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** Thiners 1031 Clear  
**Product number** 4020002

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Specialist Solvent/Thinners

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Protega Paints Ltd  
 Protega Buildings  
 Kelvin Way  
 West Bromwich  
 West Midlands B70 7JZ  
 info@protegapaints.com  
 0121 525 5665  
 0121 553 2787

##### 1.4. Emergency telephone number

**Emergency telephone** +44 121 524 2245 (not 24 hours)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 2 - H225  
**Health hazards** Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336 STOT RE 2 - H373 Asp. Tox. 1 - H304  
**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Pictogram



###### Signal word

Danger

###### Hazard statements

H225 Highly flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.  
 H312+H332 Harmful in contact with skin or if inhaled.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H335 May cause respiratory irritation.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.

## Thinners 1031 Clear

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p>
---------------------------------	--

**Contains** 1-methoxy-2-propanol, butan-1-ol, ethylbenzene

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

##### 3.2. Mixtures

<b>xylene</b> <span style="float: right;"><b>30-60%</b></span> CAS number: 1330-20-7                      EC number: 215-535-7                      REACH registration number: 01-2119488216-32-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 Skin Irrit. 2 - H315
<b>1-methoxy-2-propanol</b> <span style="float: right;"><b>10-30%</b></span> CAS number: 107-98-2                      EC number: 203-539-1                      REACH registration number: 01-2119457435-35-XXXX
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336

## Thinners 1031 Clear

<b>butan-1-ol</b>		<b>10-30%</b>
CAS number: 71-36-3	EC number: 200-751-6	REACH registration number: 01-2119484630-38-XXXX

<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H336		

<b>ethylbenzene</b>		<b>5-10%</b>
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-XXXX

<b>Classification</b>		
Flam. Liq. 2 - H225		
Acute Tox. 4 - H332		
Eye Irrit. 2 - H319		
STOT RE 2 - H373		
Asp. Tox. 1 - H304		
Aquatic Chronic 3 - H412		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	If in doubt, get medical attention promptly. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration.
<b>Ingestion</b>	Get medical attention immediately. Keep affected person warm and at rest. Do not induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.
<b>Eye contact</b>	Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	May cause respiratory irritation. Prolonged or repeated exposure may cause the following adverse effects: Coughing. May cause nausea, headache, dizziness and intoxication.
<b>Ingestion</b>	Pneumonia may be the result if vomited material containing solvents reaches the lungs. May be fatal if swallowed and enters airways. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause stomach pain or vomiting.
<b>Skin contact</b>	Causes skin irritation.

## Thinners 1031 Clear

**Eye contact** Causes serious eye irritation. Prolonged or repeated exposure may cause the following adverse effects: Pain or irritation. Profuse watering of the eyes. Redness.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

**Specific treatments** No specific chemical antidote is known to be required after exposure to this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** The product is flammable. Fire-water run-off in sewers may create fire or explosion hazard. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Control run-off water by containing and keeping it out of sewers and watercourses.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). Acrid smoke or fumes. Metal oxide(s). Oxides of nitrogen.

### 5.3. Advice for firefighters

**Protective actions during firefighting** In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Use protective equipment appropriate for surrounding materials.

**For emergency responders** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

## Thinners 1031 Clear

### Methods for cleaning up

Small Spillages: Stop leak if safe to do so. Move containers from spillage area. Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers. Large Spillages: Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Move containers from spillage area. No smoking, sparks, flames or other sources of ignition near spillage. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste via a licensed waste disposal contractor. The contaminated absorbent may pose the same hazard as the spilled material.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Note:** The information in this section contains generic advice and guidance.

#### Usage precautions

For professional users only. Eliminate all sources of ignition. Use only in well-ventilated areas. Wear protective clothing as described in Section 8 of this safety data sheet. Earth container and transfer equipment to eliminate sparks from static electricity. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Use only non-sparking tools. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

#### Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Store at temperatures between 5°C and 25°C. Store in accordance with national regulations. Store in tightly-closed, original container. Avoid contact with oxidising agents. Avoid contact with acids and alkalis. Read label before use. Avoid exposure to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly sealed when not in use.

#### Storage class

Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

##### 1-methoxy-2-propanol

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

Sk

##### butan-1-ol

## Thinners 1031 Clear

Short-term exposure limit (15-minute): WEL 50 ppm 154 mg/m<sup>3</sup>

Sk

### ethylbenzene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### xylene (CAS: 1330-20-7)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 77 mg/m <sup>3</sup> Workers - Inhalation; Short term systemic effects: 289 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 289 mg/m <sup>3</sup>
<b>PNEC</b>	- Fresh water; 0.327 mg/l - Marine water; 0.327 mg/l - Intermittent release; 0.327 mg/l - STP; 6.58 mg/l - Sediment (Freshwater); 12.46 mg/kg - Sediment (Marinewater); 12.46 mg/kg - Soil; 2.31 mg/kg

### 1-methoxy-2-propanol (CAS: 107-98-2)

<b>DNEL</b>	Industry - Inhalation; : 553.5 mg/m <sup>3</sup> Industry - Inhalation; Long term : 369 mg/m <sup>3</sup> Industry - Dermal; Long term : 50.6 mg/kg/day
<b>PNEC</b>	- Fresh water; 10 mg/l - Marine water; 1 mg/l - STP; 100 mg/l - Sediment (Freshwater); 41.6 mg/kg - Sediment (Marinewater); 4.17 mg/kg - Soil; 2.47 mg/kg

### butan-1-ol (CAS: 71-36-3)

<b>DNEL</b>	Industry - Inhalation; : 310 mg/m <sup>3</sup> Industry - Inhalation; : 100 ppm
<b>PNEC</b>	- Fresh water; 0.082 mg/l - Marine water; 0.0082 mg/l - Sediment (Freshwater); 0.178 mg/kg - Sediment (Marinewater); .0178 mg/kg - Soil; 0.015 mg/kg

### ethylbenzene (CAS: 100-41-4)

<b>DNEL</b>	Workers - Inhalation; Long term systemic effects: 77 mg/m <sup>3</sup> Workers - Inhalation; Short term local effects: 293 mg/m <sup>3</sup> Workers - Dermal; Long term systemic effects: 180 mg/kg/day
-------------	--

## 8.2. Exposure controls

## Thinners 1031 Clear

### Protective equipment



### Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for information on material and design requirements and test methods.

### Hygiene measures

Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### Respiratory protection

Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear.
Odour	Characteristic.
Flash point	21 - 32°C
Vapour density	Heavier than air.
Relative density	0.81 - 0.91
Solubility(ies)	Immiscible with water.

## Thinners 1031 Clear

### 9.2. Other information

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

**Reactivity** No test data specifically related to reactivity available for this product or its ingredients.

##### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

##### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Under normal conditions of storage and use, no hazardous reactions will occur.

##### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the accumulation of vapours in low or confined areas.

##### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with the following materials: Oxidising agents.

##### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended.

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

###### Acute toxicity - oral

**ATE oral (mg/kg)** 10,677.49

###### Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,834.62

###### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 8,339.17

#### SECTION 12: Ecological Information

##### 12.1. Toxicity

##### 12.2. Persistence and degradability

##### 12.3. Bioaccumulative potential

##### 12.4. Mobility in soil

##### 12.5. Results of PBT and vPvB assessment

##### 12.6. Other adverse effects

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

**General information** Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

**Disposal methods** Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains.



## Thinners 1031 Clear

**Waste class** 08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned.  
For further information, contact your local waste authority.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT RELATED MATERIAL
Proper shipping name (IMDG)	PAINT RELATED MATERIAL
Proper shipping name (ICAO)	PAINT RELATED MATERIAL
Proper shipping name (ADN)	PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

#### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3

## Thinners 1031 Clear

**Emergency Action Code**      •3Y

**Hazard Identification Number**    30  
(ADR/RID)

**Tunnel restriction code**          (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

#### SECTION 15: Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation**                      Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

**Health and environmental listings**      None of the ingredients are listed.

**Authorisations (Title VII Regulation 1907/2006)**      No specific authorisations are known for this product.

**Restrictions (Title VIII Regulation 1907/2006)**      No specific restrictions on use are known for this product.

##### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

**Abbreviations and acronyms used in the safety data sheet**      ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number

**Revision date**                      18/05/2015

**Revision**                              2

**Supersedes date**                  28/04/2015

**SDS number**                        5041

**Hazard statements in full**      H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

## Thinners 1031 Clear

<b>Description</b>	Epoxy Thinners/Solvent/Cleaner
<b>Shelf life</b>	1 year
<b>EU Dir 2</b>	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.